

		柱断面表（3）		A1：1/50 A3：1/100		1. 外周帯筋は溶接閉鎖型帯筋とする。 2. 〇、△は、寄せ筋を示す。 3. ○は補助筋D16を示す。						
符 号		C22	C22A	C22B	C22C	MC1	MC2	SC1・SC2	符 号	C31	C32	C32A
6階 5階	<div>Y↑ X→</div>								B1階			
									主筋	30-D32	8-D32	12-D32
									帯筋	□-D13 @100	□-D13 @100	□-D13 @100
									補助筋	仕口部の帯筋はφ100で割付ける		
									備考	符 号	C33	C34
4階	<div>Y↑ X→</div>					同 上	同 上		B1階			
									主筋	16-D32	34-D32	10-D25
									帯筋	□-D13 @100	□-D13 @100	□-D13 @100
									補助筋	仕口部の帯筋はφ100で割付ける		
									備考	符 号	C42	
3階	<div>Y↑ X→</div>					同 上	同 上		B1階			
									主筋	H-500x500x19x36	10-D25	
									帯筋	-	□-D13 @100	
									補助筋	-		
									備考	符 号	FC1	FC2
2階	<div>Y↑ X→</div>					同 上	同 上		B1階			
									主筋	44-D32	52-D32	24-D32
									帯筋	田-D16 @100	田-D16 @100	□-D16 @100
									補助筋			
									備考	符 号	FC4	FC4A
1階	<div>Y↑ X→</div>	同 上	同 上	同 上	同 上	同 上	同 上		B1階			
									主筋	26-D32	26-D32	上部 14-D32 下部 26-D32
									帯筋	□-D16 @100	□-D16 @100	□-D16 @100
									補助筋	幅止め筋はD10@1000とする		
									備考	幅止め筋はD10@1000とする		
着工 平成 28 年 6 月 25 日 竣工 令和 元年 11 月 30 日				注) 1. 鉄骨材種共通事項		印	鋼板及UH形鋼	鋼管	備考			
						無印	SM490A	STKN490B	t>40はTMCP鋼			
監理						○	SM400A	STKN400B	t>40はTMCP鋼			
						△	SS400	-	-			
施工												