

		柱断面表（1）		A1：1/50 A3：1/100		注1. 外周帯筋は溶接閉鎖型帯筋とする。 注2. 〇、△印は、寄せ筋を示す。		3. ＊は補助筋D16を示す。															
符 号		C1		C1A		C2 (C2B)		C2A		C3		C3A		C3B		C3C		C3D		C4		C4A	
6 階 5 階																							
鉄 骨		X方向 WH-800x300x16x22 Y方向 WH-800x300x16x22				WH-400x200x16x28 WT-700x300x16x28		WH-400x200x16x28 WT-700x300x16x28		WT-700x300x16x28 WH-400x200x16x28		— H-500x200x12x22		— H-500x200x12x25		WT-700x300x16x19 WH-400x200x16x19		— WH-500x200x12x28		WT-700x200x16x22 WH-850x200x16x22		WT-600x300x16x28 WH-850x200x16x28	
主 筋		12-D29				12-D29		12-D29		12-D29		14-D29		14-D29		12-D29		14-D29		12-D29		12-D29	
帯 筋		□-D13 @100				□-D13 @100		□-D13 @100		□-D13 @100		□-D13 @100		□-D13 @100		□-D13 @100		□-D13 @100		□-D13 @100		□-D13 @100	
補 助 筋		4-D16				4-D16		4-D16		4-D16		4-D16		4-D16		4-D16		4-D16		4-D16		4-D16	
備 考																							
4 階						同 上		同 上		同 上		同 上		同 上		同 上				同 上			
鉄 骨		X方向 WH-800x300x16x25 Y方向 WH-800x300x16x25																— H-500x300x16x28				WT-600x300x16x32 WH-850x200x16x36	
主 筋		12-D29																14-D29				12-D29	
帯 筋		□-D13 @100																□-D13 @100				□-D13 @100	
補 助 筋		4-D16																4-D16				4-D16	
備 考																							
3 階		同 上				同 上		同 上		同 上		同 上				同 上		同 上		同 上		同 上	
鉄 骨		X方向 WH-500x250x16x40 Y方向 WH-500x250x16x40												— WH-500x250x16x40									
主 筋		14-D29												14-D29									
帯 筋		□-D13 @100												□-D13 @100									
補 助 筋		4-D16												4-D16									
備 考																							
2 階						同 上		同 上				同 上						同 上				同 上	
鉄 骨		X方向 WH-800x300x16x28 Y方向 WH-800x300x16x28		WH-800x400x16x36 WH-800x400x16x36						WT-700x300x16x32 WH-800x200x16x32				— WH-500x200x16x36		WT-700x300x16x22 WH-400x200x16x22				WT-700x200x16x25 WH-850x200x16x25			
主 筋		12-D29		20-D29						16-D29				14-D29		12-D29				12-D29			
帯 筋		□-D13 @100		□-D13 @100						□-D13 @100				□-D13 @100		□-D13 @100				□-D13 @100			
補 助 筋		4-D16		4-D16						4-D16				4-D16		4-D16				4-D16			
備 考																							
1 階		同 上		同 上				同 上				同 上		同 上		同 上				同 上		同 上	
鉄 骨		X方向 WH-400x200x16 (19) x32 (36) Y方向 WT-700x300x16 (16) x32 (40)				WH-400x200x16 (19) x32 (36) WT-700x300x16 (16) x32 (40)				WT-700x300x16x36 WH-800x200x16x36								— WH-500x400x16x40					
主 筋						12-D29				16-D29								14-D29					
帯 筋						□-D13 @100				□-D13 @100								□-D13 @100					
補 助 筋						4-D16				4-D16								4-D16					
備 考						() 内は、C2Bを示す。																	
増工		平成 28 年 6 月 25 日		監理		日建・上田特定監理業務等共同企業体		印		鋼板及びH形鋼		鋼 管		備 考									
竣工		令和 元年 11 月 30 日		監理				無印		SM490A		STKN490B		t>40はTMCP鋼									
				監理				△		SM400A		STKN400B		t>40はTMCP鋼									
				監理				○		SS400													
				監理																			
施工		大成・大旺新洋特定建設工事共同企業体		施工																			
				注) 1. 鉄骨材種共通事項																			