

		柱断面表（2）		A1：1/50 A3：1/100		注) 1. 外周帯筋は溶接閉鎖型帯筋とする。 2. 〇、△印は、寄せ筋を示す。 3. ＊は補助筋D16を示す。							
符 号		C4B	C4C	C4D	C5	C5A	C5B	C5C	C11	C12	C21	C21A	
6 階 5 階 Y X													
	X方向	WT-700x200x16x22	WT-700x200x16x22	WT-700x200x16x28									
	Y方向	WH-850x200x16x22	WH-850x200x16x22	WH-850x200x16x28									
	主 筋	12-D29	12-D29	12-D29									
	帯 筋	□-D13 @100	□-D13 @100	□-D13 @100									
	補 助 筋	4-D16	4-D16	4-D16									
	備 考												
4 階 Y X		同 上	同 上	同 上									
3 階 Y X	同 上		同 上										
	X方向				WH-600x300x16x28	WH-600x200x16x25	WH-600x300x16x28	WH-600x300x16x32	WH-600x200x28x36	WH-800x200x28x40	H-600x300x16x32		
	Y方向				WH-600x300x16x28	WH-600x300x16x25	WH-600x200x16x28	WH-600x300x16x32	-	-	-		
	主 筋				12-D29	12-D29	12-D29	12-D29	16-D29	20-D29	12-D29		
	帯 筋				□-D13 @100	□-D13 @100	□-D13 @100	□-D13 @100	□-D13 @100	□-D13 @100	□-D13 @100		
	補 助 筋				4-D16	4-D16	4-D16	4-D16	4-D16	4-D16	4-D16		
	備 考												
2 階 Y X		同 上		同 上	同 上	同 上	同 上	同 上					
1 階 Y X	X方向		WT-700x200x16x25								H-700x300x16x32	H-700x350x16x36	
	Y方向		WH-850x200x16x25								-	-	
	主 筋		12-D29								12-D29	12-D29	
	帯 筋		□-D13 @100								□-D13 @100	□-D13 @100	
	補 助 筋		4-D16								4-D16	4-D16	
	備 考												
		同 上	同 上	同 上	同 上						同 上	同 上	
						WH-600x400x28x45	WH-600x400x28x45	WH-600x300x16x50					
						12-D29	12-D29	12-D29					
						□-D13 @100	□-D13 @100	□-D13 @100					
						4-D16	4-D16	4-D16					
着工 平成 28 年 6 月 25 日 竣工 令和 元年 11 月 30 日				注) 1. 鉄骨材種共通事項		印		鋼板及UH形鋼		鋼 管		備 考	
						無印		SM490A		STKN490B		t>40はTMCP鋼	
監理						○		SM400A		STKN400B		t>40はTMCP鋼	
						△		SS400		—		—	
施工													